



Flo Screed

Flowing, Self Levelling Screed

Description

FloScreed is a cement-based screed designed for use in the construction industry. FloScreed is designed to be used exclusively for the interior of buildings where a subsequent floor finish is to be applied.

Benefits

- **No Vibration** Flowing and Self Levelling to ensure perfect flatness
- **Ready Made Product** Delivered in a readymix truck, ready-to-use, and is installed by approved applicators using specialised pumping equipment
- **Underfloor Heating** Its high fluidity ensures complete contact with the heat source to ensure heat transfer is maximised
- **Quality Surface Finish** Superb surface finish. Needs no remedial work
- **Ready in 24Hrs** Can accommodate foot traffic in 24 hours
- **Quick and Easy** Up to 1000sq.m. can be laid by a team in a day
- **Water Resistant** Once installed and set the product is unaffected by wetting

Specification

Appearance	Grey
Compressive Strength	>20MPa
Density	2200-2300 kg/m
Drying Shrinkage	<0.60mm/m
Maintenance of Fluidity	>2hrs
Drying time @ 20°C, 60%hr	up to 2mm per day

Minimum Thickness

- **Floating over insulation** 40mm
- **Unbonded over solid base** 40mm
- **Cover over pipework** 30mm
- **Maximum Thickness** 100mm